



## **200D - DIMPLE**

**SLIP RESISTANT GRANULES - Reacts with solvent when mixed.**

### **DESCRIPTION**

Fine Clear / Opaque Dimple.

### **USES**

To increase the slip resistance of sealers on floors.

Advantages

Disperses readily and evenly through sealer.

- Polymeric in nature, therefore, more compatible physically with sealers e.g. expansion / contraction.
- Generally increases abrasion resistance of sealers.
- Compatible with solvent systems.

### **MIXING INSTRUCTIONS**

Mixing Quantities

From 50 grams/20 litre to 300 grams/20 litre.

### **MIXING**

Pour into sealer slowly, while mixing with a hand paddle.

### **APPLICATION**

Applied only into final coat of sealer.

To avoid settling, stir mix thoroughly every 2 minutes.

### **ROLLER APPLICATION**

Sealer must be roller applied from a roller tray. Do not broom apply.

Avoid excess SRA build up on the edges of the roller.

This can lead to roller lines in the surface.

To enhance slip resistance, sealer must be applied thinly, at approximately 10m<sup>2</sup> per litre.

# ALLPURPOSE COATINGS



(07) 3703 2609

Unit 12 / 10 Boron Street  
Sumner Park QLD 4074

[www.allpurposecoatings.com.au](http://www.allpurposecoatings.com.au)

## PROPERTIES

Appearance:	Clear / Opaque
Density (g/cc) @ 25°C:	0.90
Maximum Particles Size (microns):	84
Flash Point:	>277°C

## LIMITATIONS:

If left in some solvent type sealer for extended period (> 4 hours). There is a tendency for swelling and sticking together of particle.

As with most materials it will slowly wear, hence periodic check of slip resistance is advisable.

Dulls gloss retention

Supply

PC: Slip

Slip Resistant Additive – 250g

## SHELF LIFE:

A minimum of 5 years in sealed, unopened packaging when stored in cool, dry conditions.

## IMPORTANT NOTICE:

Read the MSDS and TDS carefully prior to use as application or performance data may change from time to time. In emergency, contact the Poisons Information Centre (phone 13 11 26 within Australia) or a doctor for advice.

## PRODUCT DISCLAIMER:

This Technical Data Sheet (TDS) summarises to the best of our knowledge the product, including how to use and apply the product based on the information available at the time.

You should read this TDS carefully and consider the information in the context of how you will apply the product, including if it is being used in conjunction with any other products, the type of surfaces and the manner in which the product will be applied. Our responsibility for products sold is subject to our standard terms and conditions of sale. All Purpose Coatings does not accept any liability either directly or indirectly for any losses suffered that arises from the use or application of the product