



## **500W – LIQUATHANE WATER BASED 2 PACK CLEAR URETHANE**

### **DESCRIPTION**

500W is a Water Based Two Pack Clear Urethane which is applied by roller as a clear finish. It is extremely durable, hard wearing and has little to no odour during application. For these reasons it is often used for commercial applications where solvent based products cannot be used.

### **FEATURES**

- Excellent wet look and minimal colour change.
- Extremely hard wearing.
- Low odour.
- Excellent film build.
- Excellent flow and settling characteristics.
- Roller Applied (No Foaming)
- User Friendly

### **PROPERTIES**

Mix Ratio:	4 Parts (A) 1 Parts (B)
Appearance:	Translucent. White when mixed.
Viscosity:	25 Seconds (Ford #4 cup)
Density:	1.05 g/ml
Solids Content:	35%
Flammability:	Non-Flammable.
Shelf Life:	6 Months Un-opened. (Store Between 5 - 30deg Celsius)

### **DIRECTIONS FOR USE**

All surfaces must be clean, dry, and free of wax, grease, dust and other contaminants. The presence of such contaminants contributes to conditions such as 'rejection' or 'delamination'.

Keep the edges moving in line with the roller being careful not to move too far ahead.

# ALLPURPOSE COATINGS



(07) 3703 2609

Unit 12 / 10 Boron Street  
Sumner Park QLD 4074

[www.allpurposecoatings.com.au](http://www.allpurposecoatings.com.au)

Viscosity increases with time. When making multiple mixes, combine with existing mix.

## **IMPORTANT NOTICE:**

Read the MSDS and TDS carefully prior to use as application or performance data may change from time to time. In emergency, contact the Poisons Information Centre (phone 13 11 26 within Australia) or a doctor for advice.

## **PRODUCT DISCLAIMER:**

This Technical Data Sheet (TDS) summarises to the best of our knowledge the product, including how to use and apply the product based on the information available at the time.

You should read this TDS carefully and consider the information in the context of how you will apply the product, including if it is being used in conjunction with any other products, the type of surfaces and the manner in which the product will be applied. Our responsibility for products sold is subject to our standard terms and conditions of sale. All Purpose Coatings does not accept any liability either directly or indirectly for any losses suffered that arises from the use or application of the product whether or not in accordance with any advice, specification, recommendation or information given by it.