



EPO100EP – BETTAPOXY PART B

Identification of Product & Supplier

Product: BETTAPOXY - Part B (Use in conjunction with Bettapoxy - Part A)

Classification: Hazardous according to criteria of Worksafe Australia.

Uses: Adhesive for civil engineering use, concrete repair, etc.

Supplier: All Purpose Coatings 12/10 Boron Street, Sumner Park, Queensland 4074.
sales@allpurposecoatings.com.au Phone (07) 3271 3252

Hazards Identification

Xi Irritant Risk Phrases:

R36/38 Irritating to skin and eyes. R43 May cause sensitisation by skin contact.

D.G. Class: Not classified as dangerous goods

Subsidiary Risk: Nil

Poison Schedule: S5 This product is a Schedule Poison S5 and must be stored, maintained and used in accordance with the relevant regulation.

Composition & Information on ingredients

Ingredients:

Accelerated modified Araliphatic Polyamine adduct

Ceramic Filler 14808-60-7

Other ingredients determined not to be hazardous To 100%

First Aid Measures

Poison Information Centres in each State capital can provide additional assistance for scheduled poisons. (Phone Australia 131 126)

Ingestion: If swallowed do not induce vomiting. Rinse mouth with water, give glass of water and seek medical attention.

Eye contact: Immediately irrigate with copious quantities of water for at least 15 minutes. Eyelids to be held open. Seek immediate medical assistance.

Skin contact: Remove contaminated clothing and footwear. Wash skin thoroughly with water. If swelling, redness, blistering or irritation occurs seek medical attention.

Inhalation: Remove victim from exposure to fresh air. If breathing difficulty, apply artificial respiration and seek medical attention.

Note to Physician: Treat the patient symptomatically.

Fire Fighting Measures

Extinguishing media: Water, Foam, Dry chemical powder, Carbon dioxide.

Specific Hazards: The material is stable under normal conditions. Hazardous polymerisation can occur on heating. On decomposition gives off carbon dioxide, carbon monoxide and other gases. Incompatible with alkalis, acids and strong oxidizers.



Fire Fighters: Wear positive pressure, self-contained breathing apparatus and full protective clothing.

Accidental Release Measures

Small Spills: Shut off all possible ignition sources. Wear protective equipment to prevent skin and eye contamination. Clean with absorbent material like sand, soil, vermiculite or any other inert material. Avoid contamination of drains, sewerage and waterways. Collect and seal in properly labelled containers for disposal as per local council statutory codes.

Large Spills: Shut off all possible ignition sources. Wear protective equipment to prevent skin and eye contamination. Clean with absorbent material like sand, soil, vermiculite or any other inert material. Avoid contamination of drains, sewerage and waterways. Collect and seal in properly labelled containers for disposal as per local council statutory codes. If contamination of crops, waterways, drains or sewerage has occurred, advise Emergency Services or State Department of Agriculture.

Handling and Storage

Storage: Store in the closed, original container in a cool ventilated area. Keep containers tightly closed when not in use. Keep away from explosives, food, oxidising agents and organic peroxides. This product is a Scheduled Poison S5 and must be stored, maintained and used in accordance with the relevant regulations.

Exposure Controls & Personal Protection

Exposure Limits: No value assigned for this specific product by the National Occupational and Safety Commission (Worksafe Australia).

Eng. Controls: Special ventilation is not normally required due to the low volatility of the product at normal temperature. However, in the operation of certain equipment or at elevated temperatures, mists or vapours may be generated and exhaust ventilation should be provided to maintain airborne concentration levels below the exposure standards or where no exposure standard is allocated, as low as reasonably practicable.

Personal Protection: Use overalls, safety shoes, safety goggles, rubber or chemical resistance gloves and respirator if required. Avoid skin and eye contact and the inhalation of vapour. Wear overalls, Packaging & safety goggles and impervious gloves. Available information suggests that the gloves made from PVC should be suitable for intermittent contact. However due to variations in glove construction and local conditions, the final assessment should be made by the user. If inhalation risk exists, wear organic vapour respirator meeting requirements of AS/NZS 1715 and 1716. Always wash hands with soap and water before smoking, eating, drinking or using toilet facilities. Repeated exposure may cause allergic disorders. Sensitive workers should use protective clothing. Avoid contact with eyes and skin. Do not inhale mist or vapours. After each day's use, wash gloves, safety goggles and all the contaminated clothing.



Physical & Chemical Properties

Appearance: Dark grey paste

Solubility: Partially soluble in water

Specific Gravity: 1.45 - 1.50

Boiling Point: More than 200 deg. C Rel.Vapour Density (air=1) : > 1

Melting Range: Not established

Vapour Pressure (20 o C): Less than 0.01 Pa

Decomposition Temp.(o C): More than 200 deg. C

Flash Point (o C): More than 200 deg. C (ASTM D 93)

Flammability Limits (%): Not established

Autoignition Temp. (o C): Not established

% Volatile by Volume: Nil

(All above values are Typical Values only)

Stability & Reactivity Stability

The product is stable under normal conditions and use.

Toxicological Information

No adverse health effects are expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms that may arise if the product is mishandled are:

Acute Effects:

Ingestion: Harmful if swallowed. May cause gastrointestinal discomfort and irritation.

Eye: Brief contact may cause mild irritation to eyes.

Skin: Mild irritant and poorly absorbed through the skin. Prolonged and repeated contact may cause sever irritation and/or dermatitis.

Inhaled: Not hazardous at ambient temperatures. Vapours generated at elevated temperatures or when inhaled repeatedly may cause irritation to nose, throat and respiratory tract.

Long Term Effects: Repeated skin contact and inhalation may result in sensitisation in some individuals. May cause allergic reaction, dermatitis or asthma like symptoms. Follow good working practice. Avoid ingestion, inhalation, eye and skin contact. Wash hands with soap and water before eating, drinking, smoking or using toilet facilities. Acute & Chronic Negative in a battery of mutagenicity assays.

Toxicity: No evidence of carcinogenicity was observed in long term studies of rats. No developmental nor reproductive effects in rat and rabbit. Acceptable Daily Intake (ADI) for humans is 0.01 mg/kg/day.

Ecological Information

Avoid contamination of drains, sewerage, creeks and waterways. Not toxic to aquatic organisms.



Disposal Consideration.

Dispose all empty containers as per State & Council Regulation. Do not dispose near waterways, vegetation and tree roots. Empty containers and product should not be burned.

Transport Information

UN. No.: Not Allocated

Shipping Name: Not Applicable for road, marine and air transport this product is not classified as dangerous goods within the context of National and International Transport Regulation.

Regulatory Information

The National Model Regulations for the Control of Workplace Hazardous Substances [NOHSC: 10005 (1999)]. The National Standard for the Storage and Handling of Workplace Dangerous Goods [NOHSC: 1015 (2001)].

MSDS's are updated frequently. Please ensure you have the current copy. This MSDS summarises at the date of issue our best knowledge of health and safety hazard information of the product, and in particular how to handle and use the product in the workplace. Since All Purpose Coatings Pty Ltd cannot anticipate or control the conditions under which the product may be used each user must, prior to usage, review this MSDS in the context to use and handling of the product in the workplace. If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact All Purpose Coatings Pty Ltd. Our responsibility for the product as sold is subject to our standard terms and conditions, a copy of which is available upon request.

Date of Issue: 019/02/16

This data sheet and the health, safety and environmental information it contains is considered to be accurate as of the date specified. However no warranty or representation, expressed or implied is made as to the accuracy or completeness of the data and the information in this data sheet. Health and safety precautions and environmental advice noted in this data sheet may not be accurate for all individuals and / or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. All Purpose Coatings Pty Ltd shall not be responsible for any damage of injury resulting from abnormal use of this material, from any failure to adhere to recommendations or from any hazard inherent in the nature of the material.